



DESCRIPTION

- pH::lyser eco monitors pH and temperature
- pH::lyser pro: high temperature range

FEATURES

- s::can plug and measure
- Measuring principle: Unique, non-porous / non-leaking combined reference electrode for technically unrivalled and consistent pH performance
- Multiparameter sensor
- Ideal for surface water, ground water, drinking water and wastewater
- Long-term, stable and maintenance-free operation
- Factory precalibrated
- Mounting and measurement directly in the media (in situ) or in a flow cell
- Operation via s::can terminals and s::can software
- Optional automatic cleaning with compressed air
- Plug connection or fixed cable

RECOMMENDED ACCESSORIES

PartNumber	ArticleName
D -330-xxx	con::cube V3
D -320-xxx F-	con::lyte
12-sensor F-	Carrier s::can physical probes
48-sensor	s::can sensor flow cell (bypass setup), PVC
S -11-xx-	moni::tool software

moni





TECHNICAL SPECIFICATIONS

Measuring Principle	Potentiometric	Weight (Min.)	400 g
Measuring Principle Detail	Combined, non-porous reference electrode	Dimensions (Ø × L)	33 × 257 mm
Resolution	0.01 pH	Operating Pressure	0–10 bar
Accuracy (Standard Solution)	0.1 pH	Installation/Mounting	Submersed or in a flow cell
Automatic Compensation Instrument	Temperature	Process Connection	Quick connect
Response Time (T90)	0–30 sec.	Flow Velocity	3 m/s (max.) 0.01 m/s (min.)
Integrated Temperature Sensor	0 to 90 °C	Automatic Cleaning	Media: compressed air Permissible pressure: 3–6 bar
Integration Via	con::lyte	Storage Temperature (Elec trode)	–5 to 30 °C
Power Supply	con::nect	Storage Temperature (Sensor)	–10 to 60 °C
Power Consumption (Typical)	9–18V DC	Conformity – EMC	EN 61326-1
Power Consumption	0.8 W	Conformity – Safety	EN 61010-1
Interface to s::can Terminals	1 W max.	Operating Temperature (eco)	0 to 70 °C
Cable Length	Sys plug (IP67), RS485	Operating Temperature (pro)	0 to 90 °C
Cable Type	7.5 m fixed cable (-075) or plug connection (-000)	Protection Class (-000)	IP67
Housing Material	PU jacket	Protection Class (-075)	IP68
	Stainless steel 1.4404/1.4401, POM-C or Stainless steel 1.4404/1.4401, PVC (E-514-4-075)		

MEASURING RANGE

		Parameter		
		pH [pH]	Temperature [°C]	Part Number
pH::lyser eco (pH, temp)	min.	2	0	E-514-2-000 / -075
	max.	12	70	
pH::lyser pro (pH, temp)	min.	0	0	E-514-3-000 / -075
	max.	14	90	



442 738 3918



contacto@ingframex.com



www.ingframex.com

Trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2026 Badger Meter, Inc. All rights reserved.